Oxford Pressure Sensitive

Oxford HighBright C1S is a proven choice for your prime label applications. High brightness with a blue-white shade provides the clean, crisp foundation for eye catching graphics.Oxford HighBright has been field proven in water based and UV flexographic applications in addition to standard printing formats. Combine the great surface appearance of Oxford HighBright with the high strength fiber network to ensure great converting and matrix stripping performance.



- · Smooth clean surface with excellent ink holdout
- Reliable product consistency
- High paper gloss and opacity
- Blue white shade with high brightness
- · High strength for high speed converting and matrix stripping
- Designed for Flexographic, Offset, Gravure, Letterpress and Laser printing processes

KEY PRODUCT CHARACTERISTICS

	OXFORD HIGH	OXFORD HIGH BRIGHT C1S	
BASIS WEIGHT (lbs/3300ft2)	54	58.5	
BASIS WEIGHT (GSM)	80	87	
BRIGHTNESS (TAPPI)	89	89	
GLOSS (%)	73	75	
OPACITY (%)	86	87	
SMOOTHNESS (PPS10)	0.8	0.9	
CD TENSILE (LB/IN)	16	17	
MD TEAR (GRAMS)	36	40	
CALIPER (MILS / MICRONS)	2.7 / 68	2.9 / 73	



END USE APPLICATIONS

Prime Label Charity Label Stamp Label Digital Base

Available certified chain-of-custody under FSC $^{\otimes}$, PEFC $^{\text{TM}}$ or SFI $^{\otimes}$ programs.

Available with up to 30% postconsumer waste.

CORPORATE OFFICE

1901 S. Meyers Road, Suite 600Oakbrook Terrace, IL 60181T 937-528-3870

REGIONAL OFFICE

7777 Washington Village Drive
Suite 210
Dayton, OH 45459
T 937-528-3800

For more information, visit

us.ndpaper.com

